



136KW Air Bus Indirect Diesel Oil Heater



Key Features

- High efficiency
- Strong and robust steel frame with metric bolts
- Powerful fan
- Air pressure 250 Pa (400 Pa for centrifugal version)
- Digital control of the combustion
- Unique 'cold start' button for very cold environments
- Possible connection to 4, 2 or 1 flexible tubes
- Flue gas exhaust
- Separate Riello oil burner
- Summer/Winter switch for ventilation only
- Electronic flame control with photocell
- Fan-Limit thermostat with automatic reset
- Limit thermostat with manual reset
- Fuel preheater
- Two oil filters: oil pump filter, suction filter
- Quick connector to external tank (optional)
- High-efficiency heat exchanger made of stainless steel pipes
- Stainless steel combustion chamber
- Robust wheels included
- 4 robust crane hooks

Specification

Heating Power	kW	136
	Btu/h	464,000
	kcal/h	116,900
Air Flow	m ³ /h	8,500
Fan Type	-	Axial
Air Pressure	Pa	250
Thermostat Control	-	Analogue or Digital
Fuel Consumption	l/h	12.93
Power Supply	V/ph/Hz	240/1/50
Electric Power	kW	1.5
Rated Current	A	6.9
Electronic Box Protection	IP	55
Flue Tube	Ø	200
Product Size (L x W x H)	mm	1790 x 880 x 1360
Net/Gross Weight	kg	270/300
Air Outlet Diameter	cm	4 x 27 / 1 x 60
Ancillaries Available:	Ducting, Fuel Tanks, Thermostat, Ducting Splitter, Ducting Diffusers, Power Extension Cables	

*Please note, information given is indicative and subject to change at any time