



340kW Dual Fuel Boiler

High efficiency, oil and gas fired containerised boiler



Key Features

- Can operate on either oil or gas
- Fully packaged, containerised unit
- Easy to use controls
- Runs on a single phase power supply
- Easily manoeuvrable
- Built in pressurisation unit
- Built in large expansion tank
- Can be coupled with our range of ancillaries including hoses, fittings, fuel tanks and hygienic modules/ calorifiers for DHW applications

General Data

Heating Output	kW	340
Temperature Range	°C	55-90

Operational Data

Expansion Tank	L	300
Total System Volume	L	400
Minimum Working Pressure	Bar	1
Maximum Working Pressure	Bar	6
Flow Rate	m ³ /hr	19.5
Max Oil Consumption	LPH	34
Fuel Type	-	Gas or Oil

Electrical Data

Electrical Feed	v/ph/hz	230v 1ph
Maximum Absorbed Current	A	16
Plug Type	C-Forme Plug	16a 1ph 3 pin

Physical Data

Dimensions L/W/H	mm	2440 x 2200x 2260
Weight (Empty)	kg	2500
Fluid Connections	Inch	3" Flange
Gas Connection	Inch	2" BSPF
Mains Water Connection	Inch	1/2" BSPF

*Please note, information given is indicative and subject to change at any time