



47KW Dual Voltage Indirect Diesel Oil Heater



Key Features

- High efficiency
- 100% clean, dry and fume-free warm air
- Ideal for places with limited ventilation
- Optional connection to a flexible tube
- Flue gas exhaust
- Heat exchanger
- Overheat thermostat
- Post-ventilation
- Thermally protected motor
- Three oil filters: oil pump, suction and inlet
- External suction filter with transparent glass cup
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Oil tank with level indicator
- Trolley included
- High quality brand fuel pump
- Fuel pump with access for easy maintenance
- Snorkel - breather for non-drip fuel tank
- Diagnostic LED

Specification

Heating Power	kW Btu/h kcal/h	49 167,200 42,100
Air Flow	m ³ /h	1800
Fuel Autonomy	h	14
Thermostat Control	-	Analogue or Digital
Fuel Consumption	l/h	4.7
Power Supply	V/ph/Hz	240/1/50
Electric Power	kW	0.8
Rated Current	A	3.5
Protection	IP	44
Tank Capacity	l	65
Flue Tube	∅	150/34
Product Size (L x W x H)	mm	1330 x 650 x 1000
Net/Gross Weight	kg	67/84
Dual Voltage	-	Available
Ancillaries Available:	Ducting, Fuel Tanks, Thermostat, Ducting Splitter, Ducting Diffusers, Power Extension Cables	

*Please note, information given is indicative and subject to change at any time