



630kW Dual Fuel Boiler

High efficiency, oil and gas fired containerised boiler



Key Features

- Can operate on either oil or gas
- Fully packaged, containerised unit
- Easy to use controls
- Easily manoeuvrable
- Built in pressurisation unit
- Built in large expansion tank
- Can be coupled with our range of ancillaries including hoses, fittings, fuel tanks and hygienic modules/ calorifiers for DHW applications

General Data

Heating Output	kW	630
Temperature Range	°C	55-90

Operational Data

Expansion Tank	L	600
Total System Volume	L	650
Minimum Working Pressure	Bar	1
Maximum Working Pressure	Bar	6
Flow Rate	m ³ /hr	36
Max Oil Consumption	LPH	63
Fuel Type	-	Gas or Oil

Electrical Data

Electrical Feed	v/ph/hz	400/3/50
Maximum Absorbed Current	A	32
Plug Type	C-Forme Plug	32a 3ph 5 pin

Physical Data

Dimensions L/W/H	mm	3050 x 2440 x 2590
Weight (Empty)	kg	3500
Fluid Connections	Inch	4" Flange
Gas Connection	Inch	4" BSPF
Mains Water Connection	Inch	1/2" BSPF

*Please note, information given is indicative and subject to change at any time