



730kW Chiller

Multi-scroll series: aircooled chiller with scroll compressors & Shell and Tube evaporator



Key Features

- Highly energy efficient, dual circuit, multiple scroll compressors
- Low GWP Refrigerant with massive reduction in installed power and running costs
- Internal free cooling controls & remote probe as standard
- Remote pump feed is integral on a panel mounted socket
- Lifting eyes, protective frames and fork pockets as standard
- Integral flow switch so no separate assembly required
- Units have very compact footprint due to V bank design condensers
- Operational temperature range between -10°C upto +20°C
- · Condenser coil protection grid

General Chiller Data

Cooling capacity	kW	731.4
Design Conditions	°C	Ambient: 30 / Entering: 12/ Leaving: 7
E.E.R	kW/kW	4.1
Refrigerant Gas	R	454B

Compressor Data

Compressor Type	-	Scroll	
Number of Compressors	N°	6	
Number of Circuits	N°	2	
Total Compressors Nominal Absorbed Power	kW	159.84	
Total Compressor Running Current (RLA)	А	264.06	
Capacity Steps	N°	4	

Evaporator Data

Type of Evaporator	Туре	Shell and Tube
Nominal Flow Rate	m³/h	125.42
Pressure Drop	kPa	86.00
Incoming Pressure PRV	Bar	6
System Volume	Litres	200
Hydraulic Connections	Туре	6" Flange

^{*}Please note, information given is indicative and subject to change at any time





730kW Chiller

Multi-scroll series: aircooled chiller with scroll compressors & Shell and Tube evaporator

_			_	
Р	um	าต	Da	ata

•		
Remote P3 Pump	-	Electrical Feed Included
Axial Fans and Condenser Data		
Number of Condenser Coils	N°	10
Number of Fans	N°	10
Total Air Flow	m³/h	206000
Total Electrical Data		
Nominal Absorbed Power	kW	178.24
Maximum Absorbed Current (FLA)	А	455
Maximum Starting Current (LRA)	А	613.3
Cable Type	-	Hard Wired
Electrical Feed	V/ph/Hz	400/3/50 + E (No Neutral)
Dimensions		
Length	mm	7200
Width	mm	2210
Height	mm	2500
Weight		
Empty Weight	kg	4900

Our Hire fleet also includes:











AHUs Heat Exchangers

Wide Chiller Range

Glycol Hoses & Fittings

^{*}Please note, information given is indicative and subject to change at any time