



85KW Dual Voltage Indirect Diesel Oil Heater



Key Features

- High efficiency
- 100% clean, dry and fume-free warm air
- Ideal for places with limited ventilation
- Optional connection to a flexible tube
- Flue gas exhaust
- Heat exchanger
- Overheat thermostat
- Post-ventilation
- Thermally protected motor
- Three oil filters: oil pump, suction and inlet
- External suction filter with transparent glass cup
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Oil tank with level indicator
- Trolley included
- High quality brand fuel pump
- Fuel pump with access for easy maintenance
- Snorkel - breather for non-drip fuel tank
- Diagnostic LED

Specification

Heating Power	kW Btu/h kcal/h	85 290,00 73,100
Air Flow	m ³ /h	3,300
Fuel Autonomy	h	13
Thermostat Control	-	Analogue or Digital
Fuel Consumption	l/h	8.1
Power Supply	V/ph/Hz	240/1/50
Electric Power	kW	1.06
Rated Current	A	4.6
Protection	IP	44
Tank Capacity	l	105
Flue Tube	Ø	150/41
Product Size (L x W x H)	mm	1600 x 700 x 1150
Box Size (L x W x H)	mm	1670 x 750 x 1180
Net/Gross Weight	kg	101/123
Dual Voltage	-	Available

Ancillaries Available:

Ducting, Fuel Tanks, Thermostat, Ducting Splitter,
Ducting Diffusers, Power Extension Cables

*Please note, information given is indicative and subject to change at any time